

# Package ‘adobeanalyticsr’

January 16, 2025

**Type** Package

**Version** 0.5.0

**Title** R Client for 'Adobe Analytics' API 2.0

**Description** Connect to the 'Adobe Analytics' API v2.0 <<https://github.com/AdobeDocs/analytics-2.0-apis>> which powers 'Analysis Workspace'. The package was developed with the analyst in mind, and it will continue to be developed with the guiding principles of iterative, repeatable, timely analysis.

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**Depends** R (>= 3.2.0)

**Imports** assertthat (>= 0.2.0), jsonlite (>= 1.5), dplyr (>= 0.8.1), stringr (>= 1.4.0), purrr (>= 0.3.3), httr (>= 1.3.1), tidyr (>= 1.0.0), rlang (>= 0.4.8), lubridate (>= 1.7.9), ggplot2 (>= 3.3.2), scales (>= 1.1.1), R6, jose, openssl, lifecycle, glue, vctrs, progress, memoise, utils, httr2

**Suggests** knitr, testthat (>= 3.0.0), rmarkdown

**RoxygenNote** 7.3.2

**RdMacros** lifecycle

**VignetteBuilder** knitr

**BugReports** <https://github.com/benwoodard/adobeanalyticsr/issues>

**URL** <https://github.com/benwoodard/adobeanalyticsr>

**NeedsCompilation** no

**Author** Ben Woodard [aut, cre],  
Tim Wilson [aut, ctb],  
Charles Gallagher [ctb],  
Mark Edmondson [ctb]

**Maintainer** Ben Woodard <[benwoodard@gmail.com](mailto:benwoodard@gmail.com)>

**Repository** CRAN

**Date/Publication** 2025-01-16 06:10:02 UTC

## Contents

aw_anomaly_report . . . . .	3
aw_auth . . . . .	4
aw_auth_with . . . . .	5
aw_freeform_table . . . . .	6
aw_get_calculatedmetrics . . . . .	10
aw_get_dimensions . . . . .	12
aw_get_metrics . . . . .	14
aw_get_projects . . . . .	15
aw_get_project_config . . . . .	16
aw_get_reportsuites . . . . .	17
aw_get_segments . . . . .	18
aw_get_tags . . . . .	19
aw_segment_table . . . . .	20
aw_token . . . . .	22
aw_workspace_report . . . . .	22
cm_build . . . . .	23
cm_copy . . . . .	24
cm_delete . . . . .	26
cm_formula . . . . .	27
cm_function . . . . .	27
cm_update . . . . .	28
cm_val . . . . .	29
get_cm_functions . . . . .	30
get_me . . . . .	31
get_usage_logs . . . . .	31
get_users . . . . .	33
proj_build . . . . .	33
proj_update . . . . .	34
seg_build . . . . .	35
seg_con . . . . .	37
seg_copy . . . . .	38
seg_delete . . . . .	39
seg_rule . . . . .	40
seg_seq . . . . .	42
seg_then . . . . .	43
seg_update . . . . .	44
seg_val . . . . .	45
seg_verbs . . . . .	45
tags_add . . . . .	46

**Index**

**48**

---

aw\_anomaly\_report      *Anomaly Report*

---

## Description

Get an anomaly report for one or more metrics

## Usage

```
aw_anomaly_report(
  company_id = Sys.getenv("AW_COMPANY_ID"),
  rsid = Sys.getenv("AW_REPORTSUITE_ID"),
  date_range = c(Sys.Date() - 31, Sys.Date() - 1),
  metrics,
  granularity = "day",
  segmentId = NA,
  quickView = FALSE,
  anomalyDetection = TRUE,
  countRepeatInstances = TRUE,
  debug = FALSE
)
```

## Arguments

company_id	Company Id. Taken from the global environment by default if not provided.
rsid	Adobe report number
date_range	A two length vector of start and end Date objects (default set to show last 30 days)
metrics	Metric to request the anomaly detection. If multiple metrics, each metric and date will have it's own row.
granularity	Use either hour, day (default), week, or month
segmentId	Use segments to globally filter the results. Use 1 or many.
quickView	Return a list of 3 lists per metric. 1. All Data 2. Data filtered to include only anomalous rows 3. Interactive ggplot line graph
anomalyDetection	logical statement for including anomaly. Default is TRUE
countRepeatInstances	Should the data include repeat instances
debug	default is FALSE but set to TRUE to see the json request being sent to the Adobe API

**Value**

If quickView = 'FALSE' (default) then a data frame including the day, metric, data, dataExpected, dataUpperBound, dataLowerBound, and dataAnomalyDetected will be returned. If quickView = 'TRUE' then a list of three lists will be returned. The first list will be a data frame including all the default columns. The second list item will be a filtered data frame that includes rows where dataAnomalyDetected = 'TRUE'. The third list item is a visual made using 'ggplot2' with the error band and points where the dataAnomalyDetected = 'TRUE'. If more than one metric is in the request and quickView is set to TRUE then the lists will be split by each metric requested.

---

aw\_auth

*Generate an Access Token for the Adobe Analytics v2.0 API*


---

**Description**

**Note:** aw\_auth() is the primary function used for authorization. auth\_oauth() and auth\_s2s() should typically not be called directly.

**Usage**

```
aw_auth(type = aw_auth_with(), ...)

auth_jwt(
  file = Sys.getenv("AW_AUTH_FILE"),
  private_key = Sys.getenv("AW_PRIVATE_KEY"),
  jwt_token = NULL,
  ...
)

auth_s2s(
  file = Sys.getenv("AW_AUTH_FILE"),
  s2s_token = NULL,
  type = "s2s",
  ...
)

auth_oauth(
  client_id = Sys.getenv("AW_CLIENT_ID"),
  client_secret = Sys.getenv("AW_CLIENT_SECRET"),
  use_oob = TRUE
)
```

**Arguments**

type	Either 's2s' or 'oauth'. This can be set explicitly, but a best practice is to run aw_auth_with() to set the authorization type as an environment variable before running aw_auth()
------	---

...	Additional arguments passed to auth functions.
file	A JSON file containing service account credentials required for JWT authentication. This file can be downloaded directly from the Adobe Console, and should minimally have the fields API_KEY, CLIENT_SECRET, ORG_ID, and TECHNICAL_ACCOUNT_ID.
private_key	Filename of the private key for JWT authentication.
jwt_token	(Optional) A custom, encoded, signed JWT claim. If used, client_id and client_secret are still required.
s2s_token	(Optional) A custom, encoded, S2S authentication token.
client_id	The client ID, defined by a global variable or manually defined
client_secret	The client secret, defined by a global variable or manually defined
use_oob	if FALSE, use a local webserver for the OAuth dance. Otherwise, provide a URL to the user and prompt for a validation code. Defaults to the value of the http_oob_default default, or TRUE if httpuv is not installed.

**Value**

The path of the cached token. This is returned invisibly.

**Functions**

- `auth_jwt()`: Authenticate with JWT token
- `auth_s2s()`: Authenticate with S2S token
- `auth_oauth()`: Authorize via OAuth 2.0

**See Also**

[aw\\_auth\\_with\(\)](#)

---

aw_auth_with	<i>Set authorization options</i>
--------------	----------------------------------

---

**Description**

**Get** or **set** various authorization options. If called without an argument, then these functions return the current setting for the requested option (which can be NULL if the option has not been set). To clear the setting, pass NULL as an argument.

`aw_auth_with` sets the type of authorization for the session. This is used as the default by `aw_auth()` when no specific option is given.

`aw_auth_path` sets the file path for the cached authorization token. It should be a directory, rather than a filename. If this option is not set, the current working directory is used instead.

`aw_auth_name` sets the file name for the cached authorization token. If this option is not set, the default filename is `aw_auth.rds`

**Usage**

```
aw_auth_with(type)
```

```
aw_auth_path(path)
```

```
aw_auth_name(name)
```

**Arguments**

type	The authorization type: 'oauth', 's2s', or 'jwt'
path	The location for the cached authorization token. It should be a directory, rather than a filename. If this option is not set, the current working directory is used instead. If the location does not exist, it will be created the first time a token is cached.
name	The filename, such as aw_auth.rds for the cached authorization token file. The file is stored as an RDS file, but there is no requirement for the .rds file extension. .rds is not appended automatically.

**Value**

The option value, invisibly

**See Also**

[aw\\_auth\(\)](#)

---

aw\_freeform\_table      *Get a freeform table*

---

**Description**

Get a report analogous to a **Freeform Table** visualization in Analysis Workspace. The function uses the arguments to construct and execute a JSON-based query to the Adobe Analytics API and then returns the results as a data frame.

**Usage**

```
aw_freeform_table(  
  company_id = Sys.getenv("AW_COMPANY_ID"),  
  rsid = Sys.getenv("AW_REPORTSUITE_ID"),  
  date_range = c(Sys.Date() - 30, Sys.Date() - 1),  
  dimensions = c("page", "lasttouchchannel", "mobiledevicetype"),  
  metrics = c("visits", "visitors"),  
  top = c(5),  
  page = 0,  
  filterType = "breakdown",
```

```

    segmentId = NA,
    metricSort = "desc",
    include_unspecified = TRUE,
    search = NA,
    prettynames = FALSE,
    debug = FALSE,
    check_components = TRUE
)

```

## Arguments

company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renvi ron or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me()</a> to get a list of available company_id values.
rsid	Adobe report suite ID (RSID). If an environment variable called AW_REPORTSUITE_ID exists in .Renvi ron or elsewhere and no rsid argument is provided, then the AW_REPORTSUITE_ID value will be used. Use <a href="#">aw_get_reportsuites()</a> to get a list of available rsid values.
date_range	A length-2 vector with a start date and an end date. POSIXt objects are sent as is, for fine control over the date range. Numeric values are automatically converted to dates.
dimensions	A character vector of dimensions. There is currently a limit of 20 dimension breakdowns. Each dimension value that gets broken down by another dimension requires an additional API call, so the more dimensions that are included, the longer the function will take to return results. This is how the Adobe Analytics API works. Use <a href="#">aw_get_dimensions()</a> to get a list of available dimensions IDs.
metrics	A character vector of metrics. Use <a href="#">aw_get_metrics()</a> and <a href="#">aw_get_calculatedmetrics()</a> to get a list of available metrics IDs.
top	The number of values to be pulled for each dimension. The default is 5 and the "top" is based on the first metric value (along with metricSort). If there are multiple dimensions, then this argument can either be a vector that includes the number of values to include at each level (each breakdown) or, if a single value is used, then that will be the maximum number of values to return at each level. See the <b>Details</b> for information on the unique handling of daterange... values.
page	Used in combination with top to return the next page of results. Uses 0-based numbering (e.g., top = 50000 and page = 1 will return the top 50,000 items <i>starting at 50,001</i> ).
filterType	This is a placeholder argument for use as additional functionality is added to the package. Currently, it defaults to breakdown, and that is the only supported value.
segmentId	A single segment ID or a vector of multiple segment IDs to apply to the overall report. If multiple segmentId values are included, the segments will be effect-ived ANDed together, just as if multiple segments were added to the header of an Analysis Workspace panel. Use <a href="#">aw_get_segments()</a> to get a list of available segmentId values.

metricSort	Pre-sorts the table by metrics. Values are either asc (ascending) or desc (descending).
include_unspecified	Whether or not to include <b>Unspecified</b> values in the results. This is the equivalent of the <b>Include Unspecified (None)</b> checkbox in freeform tables in Analysis Workspace. This defaults to TRUE, which includes <b>Unspecified</b> values in the results.
search	Criteria to filter the results by one or more dimensions. Searches are case-insensitive. Refer to the <b>Details</b> for more information on constructing values for this argument.
prettyNames	A logical that determines whether the column names in the results use the API field name (e.g., "mobiledevicetype", "pageviews") or the "pretty name" for the field (e.g., "Mobile Device Type", "Page Views"). This applies to both dimensions and metrics. The default value is FALSE, which returns the API field names. For custom eVars, props, and events, the non-pretty values are simply the variable number (e.g., "evar2", "prop3", "event15"). If TRUE, undoes any efficiency gains from setting check_components to FALSE.
debug	Set to TRUE to publish the full JSON request(s) being sent to the API to the console when the function is called. The default is FALSE.
check_components	Specifies whether to check the validity of metrics and dimensions before running the query. This defaults to TRUE, which triggers several additional API calls behind the scenes to retrieve all dimensions and metrics from the API. This has a nominal performance impact and may not be ideal if you are running many queries. If you have many queries, consider implementing validity checking through other means (manually or within the code) and then set this value to FALSE.

## Details

This function is based on the **Freeform Table** visualization in Analysis Workspace. It is accessing the same API call type that is used to generate those visualizations.

### Dimension Ordering:

Adobe Analytics only queries one dimension at a time, even though the results get returned in a single data frame (or table in the case of Analysis Workspace). The more dimensions are included in the report—the more breakdowns of the data—the more queries are required. As a result, the *order* of the dimensions *can* have a dramatic impact on the total query time, even if the resulting data is essentially identical.

One way to understand this is to consider how much dragging and dropping would be required to return the data in Analysis Workspace.

Consider a scenario where you are pulling metrics for the last 30 days (daterangeday) for **Mobile Device Type** (mobiledevicetype), which has 7 unique values. Setting dimensions = c("daterangeday", "mobiledevicetype") would make one query to get the values of the 30 days included. The query would then run a separate query for *each of those 30 days* to get the mobiledevicetype results for each day. So, this would be **31 API calls**.

If, instead, the function was called with the dimension values reversed (dimensions = c("mobiledevicetype", "daterangeday")), then the first query would return the 7 mobiledevicetype values, and then



would run an additional query for each of those 7 *mobile device type values* to return the results for the 30 days within each device type. This would be only **7 API calls**.

Strategically ordering dimensions—and then wrangling the resulting data set as needed—is one of the best ways to improve query performance.

### Date Handling:

Date handling has several special characteristics that are worth getting familiar with:

- The API names for day, week, month, etc. are prepended with `daterange`, so daily data uses `daterangeday`, weekly data uses `daterangeweek`, monthly data uses `daterangemonth`, etc.
- When setting the argument for `top`, if the first (or only) dimension value is a `daterange` . . . object, then, if this argument is not explicitly specified *or* if it uses only a single value (e.g., `top = 10`), the function will still return all of the values that fall in that date range. For instance, if the `date_range` was set for a 30-day period and the first dimension value was `daterangeday`, *and* no value is specified for `top`, rather than simply returning the first 5 dates in the range, all 30 days will be returned. In the same scenario, if `top = 10` was set, then all 30 days would still be returned, and the 10 would simply be applied to the additional dimensions.
- If you want to return all of the date/time values but then have specific control over the number of values returned for each of the drilldown dimensions, then set `0` as the first value in the `top` argument and then specify different numbers for each breakdown (e.g., `top = c(0, 3, 10)` would return all of the date/time values for the specified `date_range`, the top 3 values for the second specified dimension, and then the top 10 values for each of the next dimension's results).
- If you are using a `daterange` . . . value *not* as the first dimension, then simply using `0` at the same level in the `top` argument specification will return all of the values for that date/time value.

### Search/Filtering:

There are powerful filtering abilities within the function. However, to support that power requires a syntax that can feel a bit cumbersome for simple queries. **Note:** search filters are case-insensitive. This is Adobe Analytics API functionality and can not be specified otherwise in queries.

The `search` argument takes a vector of search strings, with each value in the vector corresponding to the dimension value that is at the same position. These search strings support a range of operators, including AND, OR, NOT, MATCH, CONTAINS, BEGINS-WITH, and ENDS-WITH.

The default for any search string is to use CONTAINS. Consider a query where `dimensions = c("mobiledevicetype", "lasttouchchannel")`:

- `search = "CONTAINS 'mobile'"` will return results where `mobiledevicetype` contains "mobile", so would return all rows for **Mobile Phone**.
- This could be shortened to `search = "'mobile'"` and would behave exactly the same, since CONTAINS is the default operator
- `search = c("CONTAINS 'mobile'", "CONTAINS 'search'")` will return results where `mobiledevicetype` contains "mobile" and, within those results, results where `lasttouchchannel` contains "search".
- `search = c("(CONTAINS 'mobile') OR (CONTAINS 'tablet')", "(MATCH 'paid search')")` will return results where `mobiledevicetype` contains "mobile" *or* "tablet" and, within those results, will only include results where `lasttouchchannel` exactly matches "paid search" (but is case-insensitive, so would return "Paid Search" values).

**Value**

A data frame with the specified dimensions and metrics.

**See Also**

[get\\_me\(\)](#), [aw\\_get\\_reportsuites\(\)](#), [aw\\_get\\_segments\(\)](#), [aw\\_get\\_dimensions\(\)](#), [aw\\_get\\_metrics\(\)](#), [aw\\_get\\_calculatedmetrics\(\)](#), [aw\\_segment\\_table\(\)](#)

---

aw\_get\_calculatedmetrics

*Get a list of calculated metrics.*

---

**Description**

Retrieve a list of available calculated metrics. The results will always include these default items: id, name, description, rsid, owner, polarity, precision, type. Other attributes can be optionally requested through the expansion field.

**Usage**

```
aw_get_calculatedmetrics(  
  company_id = Sys.getenv("AW_COMPANY_ID"),  
  rsids = NULL,  
  ownerId = NULL,  
  filterByIds = NULL,  
  toBeUsedInRsid = NULL,  
  locale = "en_US",  
  name = NULL,  
  tagNames = NULL,  
  favorite = NULL,  
  approved = NULL,  
  limit = 1000,  
  page = 0,  
  sortDirection = "DESC",  
  sortProperty = NULL,  
  expansion = NULL,  
  includeType = "all",  
  debug = FALSE  
)
```

**Arguments**

**company\_id** Company ID. If an environment variable called AW\_COMPANY\_ID exists in `.Renvi ron` or elsewhere and no `company_id` argument is provided, then the AW\_COMPANY\_ID value will be used. Use [get\\_me](#) to get a list of available `company_id` values.

rsids	Filter the list to only include calculated metrics tied to a specified RSID or list of RSIDs. Specify multiple RSIDs as a vector (i.e., "rsids = c("rsid_1", rsid_2", ...rsid_n)"). Use <a href="#">aw_get_reportsuites</a> to get a list of available rsid values.
ownerId	Filter the list to only include calculated metrics owned by the specified loginId.
filterByIds	Filter the list to only include calculated metrics in the specified list as specified by a single string or as a vector of strings.
toBeUsedInRsid	The report suite where the calculated metric is intended to be used. This report suite is used to determine things like compatibility and permissions. If it is not specified, then the permissions will be calculated based on the union of all metrics authorized in all groups the user belongs to. If <b>compatibility</b> is specified for expansion, and toBeUsedInRsid is not, then the compatibility returned is based off of the compatibility from the last time the calculated metric was saved.
locale	The locale that system-named metrics should be returned in. Non-localized values will be returned for title, name, description, etc. if a localized value is not available.
name	Filter the list to only include calculated metrics that contain the specified <b>name</b> . This is case-insensitive and is a simple, single string match.
tagNames	Filter the list to only include calculated metrics that contain one of the tags as specified by a single string or vector of strings.
favorite	Set to TRUE to only include calculated metrics that are favorites in the results. A value of FALSE will return all calculated metrics, including those that are favorites.
approved	Set to TRUE to only include calculated metrics that are approved in the results. A value of FALSE will return all calculated metrics, including those that are approved and those that are not.
limit	The number of results to return per page. The default is 1,000.
page	The "page" of results to display. This works in conjunction with the limit argument and is zero-based. For instance, if limit = 10 and page = 1, the results returned would be 11 through 20.
sortDirection	The sort direction for the results: ASC (default) for ascending or DESC for descending. (This is case insensitive, so asc and desc work as well.)
sortProperty	The property to sort the results by. Currently available values are id (default), name, and modified_date. Note that setting expansion = modified returns results with a column added called modified, which is the last date the calculated metric was modified. When using this value for sortProperty, though, the name of the argument is modified_date, because why would we expect locked-in consistency from Adobe?
expansion	Additional calculated metric metadata fields to include in the results: reportSuiteName, ownerFullName, modified, tags, definition, compatability, categories. See <b>Details</b> for more information about the quirks of this argument.
includeType	Include additional calculated metrics not owned by user. Available values are all (default), shared, and templates. The all option takes precedence over "shared"
debug	Include the output and input of the api call in the console for debugging. Default is FALSE

## Details

This function is useful/needed to identify the specific ID of a calculated metric for use in other functions like `aw_freeform_report`.

The `expansion` argument accepts the following values, which will then include additional columns in the results:

- **ownerFullName**: adds `owner.name` and `owner.login` columns to the results (`owner.id` is already included by default).
- **modified**: adds a `modified` column to the output with the date (ISO 8601 format) each calculated metric was last modified.
- **definition**: adds *multiple* columns (the number will vary based on the number and complexity of calculated metrics returns) that provide the actual formula for each of the calculated metrics. This is returned from the API as a JSON object and converted into columns by the function, which means it is pretty messy, so, really, it's not recommended that you use this value.
- **compatability**: should add a column with the products that the metric is compatible with, but this behavior has not actually been shown to be true, so this may actually do nothing if included.
- **reportSuiteName**: adds a `reportSuiteName` and a `siteTitle` column with the friendly report suite name for the RSID.
- **tags**: adds a column with an embedded data frame with all of the existing tags that are associated with the calculated metric. This can be a bit messy to work with, but the information is, at least, there.

Multiple values for `expansion` can be included in the argument as a vector. For instance, `expansion = c("tags", "modified")` will add both a `tags` column and a `modified` column to the output.

## Value

A data frame of calculated metrics and their metadata.

## See Also

[aw\\_get\\_metrics](#)

---

aw_get_dimensions	<i>Get list of dimensions</i>
-------------------	-------------------------------

---

## Description

This will generate an extensive list of all the dimensions in the reportsuite.

**Usage**

```
aw_get_dimensions(
  rsid = Sys.getenv("AW_REPORTSUITE_ID"),
  locale = "en_US",
  segmentable = FALSE,
  reportable = FALSE,
  classifiable = FALSE,
  expansion = NULL,
  debug = FALSE,
  company_id = Sys.getenv("AW_COMPANY_ID")
)
```

**Arguments**

rsid	Adobe report suite ID (RSID). If an environment variable called AW_REPORTSUITE_ID exists in .Renvirom or elsewhere and no rsid argument is provided, then the AW_REPORTSUITE_ID value will be used. Use <a href="#">aw_get_reportsuites</a> to get a list of available rsid values.
locale	The locale that dimension details should be returned in. The default is en_US.
segmentable	Boolean that determines whether or not to include dimensions that can be used in segments. FALSE (the default) returns <i>all</i> dimensions ( <i>not</i> just the non-segmentable ones). Examples of dimensions that cannot be used in segments are clickmapaction, codeversion, newvisit, and pageurl.
reportable	Boolean that determines whether or not to include dimensions that can be used in reports FALSE (the default) returns <i>all</i> dimensions ( <i>not</i> just the non-segmentable ones).
classifiable	Boolean that determines whether or not to include dimensions that can be used in classifications FALSE (the default) returns <i>all</i> dimensions ( <i>not</i> just the non-segmentable ones).
expansion	Additional dimension metadata to include in the results: tags, allowedForReporting, and categories. This argument takes a single value (e.g., expansion = "tags") or a vector of values (e.g., expansion = c("tags", "categories")).
debug	Include the output and input of the api call in the console for debugging. Default is FALSE
company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renvirom or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me</a> to get a list of available company_id values.

**Value**

A data frame of dimensions and their meta data.

---

aw_get_metrics	<i>Get list of metrics</i>
----------------	----------------------------

---

### Description

Get a data frame with all of the standard (non-calculated) metrics (measures) in the report suite.

### Usage

```
aw_get_metrics(
  rsid = Sys.getenv("AW_REPORTSUITE_ID"),
  locale = "en_US",
  segmentable = "NULL",
  expansion = NULL,
  company_id = Sys.getenv("AW_COMPANY_ID"),
  debug = FALSE
)
```

### Arguments

rsid	Adobe report suite ID (RSID). If an environment variable called AW_REPORTSUITE_ID exists in .Renviron or elsewhere and no rsid argument is provided, then the AW_REPORTSUITE_ID value will be used. Use <a href="#">aw_get_reportsuites</a> to get a list of available rsid values.
locale	The locale that system-named metrics should be returned in. Non-localized values will be returned for title, name, description, etc. if a localized value is not available.
segmentable	Boolean that determines whether or not to include metrics that can be used in segments. NULL (the default) and FALSE return <i>all</i> metrics ( <i>not</i> just the non-segmentable ones). Examples of metrics that cannot be used in segments are bounces, bounce rate, entries, and visitors.
expansion	Additional metrics metadata to include in the results: tags, allowedForReporting, and categories. This argument takes a single value (e.g., expansion = "tags") or a vector of values (e.g., expansion = c("tags", "categories")).
company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renviron or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me</a> to get a list of available company_id values.
debug	Include the output and input of the api call in the console for debugging. Default is FALSE

### Details

This function is commonly used to get the correct ID for a specific metric or metrics that will be used in other function calls. The results returned are:

- All of the "out of the box" metrics like visits, page views, visitors, orders, revenue, bounce rate, etc.
- All of the enabled events that are configured in the report suite.
- An instances metric for each enabled eVar.

This function does *not* return calculated metrics.

### Value

A data frame of metrics (excluding calculated metrics) and their meta data.

### See Also

[aw\\_get\\_calculatedmetrics](#)

---

aw_get_projects	<i>Pull a list of projects</i>
-----------------	--------------------------------

---

### Description

A list of projects in the account

### Usage

```
aw_get_projects(
  includeType = "all",
  expansion = NULL,
  locale = "en_US",
  limit = 1000,
  page = 0,
  debug = FALSE,
  company_id = Sys.getenv("AW_COMPANY_ID")
)
```

### Arguments

includeType	Include additional projects not owned by user. The "all" option takes precedence over "shared". If neither guided, or project is included, both types are returned
expansion	Comma-delimited list of additional project metadata fields to include on response. Available values : reportSuiteName, ownerFullName, modified, tags, accessLevel, externalReferences, definition
locale	Locale Default value : en_US
limit	Number of results per page. Default value: 1000
page	Page number (base 0 - first page is "0")
debug	Set to TRUE to publish the full JSON request(s) being sent to the API to the console when the function is called. The default is FALSE.

company\_id      Company ID. If an environment variable called AW\_COMPANY\_ID exists in .Renvi ron or elsewhere and no company\_id argument is provided, then the AW\_COMPANY\_ID value will be used. Use [get\\_me\(\)](#) to get a list of available company\_id values.

### Value

A data frame

---

aw\_get\_project\_config *Pull a project configuration*

---

### Description

Returns a project configuration json string

### Usage

```
aw_get_project_config(
  projectId = NULL,
  expansion = NULL,
  locale = "en_US",
  debug = FALSE,
  company_id = Sys.getenv("AW_COMPANY_ID")
)
```

### Arguments

projectId	The Project id for which to retrieve information
expansion	Comma-delimited list of additional project metadata fields to include on response. Available values : reportSuiteName, shares, tags, accessLevel, modified, externalReferences, definition
locale	Locale Default value : en_US
debug	Set to TRUE to publish the full JSON request(s) being sent to the API to the console when the function is called. The default is FALSE.
company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renvi ron or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me()</a> to get a list of available company_id values.

### Value

A json string



---

aw\_get\_reportsuites     *Get list of report suites*

---

## Description

Retrieve a list of report suites and meta data about each one.

## Usage

```
aw_get_reportsuites(
  company_id = Sys.getenv("AW_COMPANY_ID"),
  rsids = NULL,
  rsidContains = NULL,
  limit = 10,
  page = 0,
  expansion = NULL,
  debug = FALSE
)
```

## Arguments

company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renviron or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me</a> to get a list of available company_id values.
rsids	Filter the results to include one or more specific report suites. Specify multiple RSIDs as a vector (i.e., "rsids = c("rsid_1", rsid_2", ...rsid_n)").
rsidContains	Filter the results list to only include suites that contain the specified string within the RSID. This is case-insensitive and is a simple, single string match.
limit	The number of results to return per page. This argument works in conjunction with the page argument. The default is 10.
page	The "page" of results to display. This works in conjunction with the limit argument and is zero-based. For instance, if limit = 20 and page = 1, the results returned would be 21 through 40.
expansion	Additional segment metadata fields to include in the results: name, parentRsid, currency, calendarType, timezoneZoneinfo. This argument takes a single value (e.g., expansion = "name") or a vector of values (e.g., expansion = c("name", "currency")).
debug	Include the output and input of the api call in the console for debugging. Default is FALSE

## Value

A data frame of report suites and their meta data.

---

aw_get_segments	<i>Get a list of segments</i>
-----------------	-------------------------------

---

## Description

Retrieve all segments or a filtered list of segments

## Usage

```
aw_get_segments(
  company_id = Sys.getenv("AW_COMPANY_ID"),
  rsids = NULL,
  segmentFilter = NULL,
  locale = "en_US",
  name = NULL,
  tagNames = NULL,
  filterByPublishedSegments = "all",
  limit = 10,
  page = 0,
  sortDirection = "ASC",
  sortProperty = "id",
  expansion = NULL,
  includeType = "all",
  debug = FALSE
)
```

## Arguments

company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renvi on or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get-me</a> to get a list of available company_id values.
rsids	Filter the list to only include segments tied to a specified RSID or list of RSIDs. Specify multiple RSIDs as a vector (i.e., "rsids = c("rsid_1", rsid_2", ...rsid_n)"). Use <a href="#">aw_get_reportsuites</a> to get a list of available rsid values.
segmentFilter	Filter list to only include segments in the list of segment IDs (comma-delimited)
locale	The locale that segment details should be returned in. The default is en_US.
name	Filter the list to only include segments that contain the specified <b>name</b> . This is case-insensitive and is a simple, single string match.
tagNames	Filter the list to only include segments that contain one of the tags.
filterByPublishedSegments	Filter the list to only include segments where the published field is set to one of the allowable values: all (the default), TRUE, or FALSE.
limit	The number of results to return per page. This argument works in conjunction with the page argument. The default is 10.

page	The "page" of results to display. This works in conjunction with the limit argument and is zero-based. For instance, if limit = 20 and page = 1, the results returned would be 21 through 40.
sortDirection	The sort direction for the results: ASC (default) for ascending or DESC for descending. (This is case insensitive, so asc and desc work as well.)
sortProperty	The property to sort the results by. Currently available values are id (default), name, and modified_date. Note that setting expansion = modified returns results with a column added called modified, which is the last date the calculated metric was modified. When using this value for sortProperty, though, the name of the argument is modified_date, because why would we expect locked-in consistency from Adobe?
expansion	Additional segment metadata fields to include in the results: reportSuiteName, ownerFullName, modified, tags, compatibility, definition, publishingStatus, definitionLastModified, and categories. This argument takes a single value (e.g., expansion = "modified") or a vector of values (e.g., expansion = c("modified", "ownerFullName")).
includeType	Include additional segments not owned by the user. Available values are all (default), shared, and templates. The all option takes precedence over "shared".
debug	Include the output and input of the api call in the console for debugging. Default is FALSE

**Value**

A data frame of segments and their meta data.

---

aw_get_tags	<i>Get a list of tags</i>
-------------	---------------------------

---

**Description**

Retrieve all tag names or search by component id or tag names

**Usage**

```
aw_get_tags(
  company_id = Sys.getenv("AW_COMPANY_ID"),
  componentId = NULL,
  componentType = NULL,
  tagNames = NULL,
  limit = 1000,
  page = 0,
  debug = FALSE
)
```

**Arguments**

company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renvi ron or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me</a> to get a list of available company_id values.
componentId	The component id being requested. Default is NULL
componentType	The component type being requested. Options include segment, dashboard, bookmark, calculatedMetric, project, dateRange, metric, dimension, virtualReportSuite, scheduledJob, alert, classification. Default is NULL
tagNames	Comma separated vector of tag names. componentType
limit	The number of results to return per page. This argument works in conjunction with the page argument. The default is 10.
page	The "page" of results to display. This works in conjunction with the limit argument and is zero-based. For instance, if limit = 20 and page = 1, the results returned would be 21 through 40.
debug	Include the output and input of the api call in the console for debugging. Default is FALSE

**Value**

A data frame of tags and the associated meta data.

---

aw_segment_table	<i>Get a segment-row freeform table</i>
------------------	---

---

**Description**

This is the equivalent of a freeform table with segments as the row components. This type of table offers a few components that aw\_freeform\_table does not. For example, this function does not require (or allow) dimensions to be included in the breakdown. Segment IDs are automatically translated into their human-readable names.

**Usage**

```
aw_segment_table(
  company_id = Sys.getenv("AW_COMPANY_ID"),
  rsid = Sys.getenv("AW_REPORTSUITE_ID"),
  segmentRsids,
  date_range = c(Sys.Date() - 30, Sys.Date() - 1),
  metrics = c("visits", "visitors"),
  globalSegment = NULL,
  segmentIds = NULL,
  debug = FALSE
)
```

**Arguments**

company_id	Company ID
rsid	Report suite ID for the data pull
segmentRsids	Deprecated.
date_range	Date range
metrics	Metrics to request for each segment
globalSegment	One or more segments to apply globally over all other segments
segmentIds	One or more segments that will compose the rows of the table
debug	Logical, whether to make verbose requests to the API and view the whole exchange

**Details**

This is a specialized function. To see segments broken down by dimensions, we recommend making multiple requests to `aw_freeform_table` with different global segments applied, and then row-binding them together yourself.

Unlike `aw_freeform_table`, this function automatically handles the 10-metric restriction imposed by the API.

**Efficiency:**

In short, segments are cheap, metrics are expensive. Adding 1 metric is the equivalent of adding 10 segments, judging by the number of requests necessary to collect the data.

**Stacking segments:**

The function does not currently support segment breakdowns, but you can stack segments by applying a global segment to your query.

**Value**

`tibble::tibble()` of segments and metrics. Rows are returned with segments in the order they were requested, not by metric sorting.

**See Also**

`aw_freeform_table()`

---

aw_token	<i>OAuth2 Token for Adobe Analytics (deprecated)</i>
----------	--

---

### Description

This is the legacy mechanism for retrieving the authorization token using OAuth. It has been replaced by `aw_auth()`.

**[Deprecated]**

### Usage

```
aw_token(
  client_id = Sys.getenv("AW_CLIENT_ID"),
  client_secret = Sys.getenv("AW_CLIENT_SECRET"),
  use_oob = TRUE
)
```

### Arguments

<code>client_id</code>	defined by global variable or manually defined
<code>client_secret</code>	defined by global variable or manually defined
<code>use_oob</code>	for the purpose of testing. Default is set to TRUE

### Value

An authorization token is saved the file name `aa.oauth`. If the file `aa.oauth` does not exist then one will be created at the end of the authorization process.

### See Also

[aw\\_auth\(\)](#)

---

aw_workspace_report	<i>Use a prebuilt json query to pull a ranked report</i>
---------------------	--

---

### Description

Organizes the arguments into a json string and then structures the data after the internal function makes the api call. Only runs a single dimension with as many metrics as you want.

### Usage

```
aw_workspace_report(req_body = "", company_id = Sys.getenv("AW_COMPANY_ID"))
```

**Arguments**

req_body	The json string copied from Workspace
company_id	Company Id. Taken from the global environment by default if not provided.

**Value**

A data frame of dimensions and metrics

---

cm_build	<i>Build a Calculated Metric</i>
----------	----------------------------------

---

**Description**

This function combines formulas to create calculated metrics in Adobe Analytics

**Usage**

```
cm_build(
  name = NULL,
  description = NULL,
  formula = NULL,
  seg_filter = NULL,
  polarity = "positive",
  precision = 0,
  type = "decimal",
  create_cm = FALSE,
  tagNames = NULL,
  internal = FALSE,
  debug = FALSE,
  rsid = Sys.getenv("AW_REPORTSUITE_ID"),
  company_id = Sys.getenv("AW_COMPANY_ID")
)
```

**Arguments**

name	This is the name of the new calculated metric (required)
description	This is the description of the segment (optional)
formula	Formulas are list objects created using the <code>cm_formula()</code> function.
seg_filter	A segment filter to be added to a metric in the formula
polarity	Also known as 'Show Upward Trend As' in the UI. Options include 'positive' (default) or 'negative'. This metric polarity setting shows whether Analytics should consider an upward trend in the metric as good (green) or bad (red). As a result, the report's graph will show as green or red when it's going up.
precision	Shows how many decimal places will be shown in the report. The maximum number of decimal places you can specify is 10. Also known as 'Decimal Places' in the UI. Default is 0. Must be a numeric.

type	Choices include Decimal (default), Time, Percent, and Currency. Also known as 'Format' in the UI.
create_cm	Used to determine if the segment should be created in the report suite or if the definition should be returned to be validated using cm_validate. Default is FALSE
tagNames	Apply tag names to the newly created calculated metric. Single string or a vector.
internal	Determines if this segment is to be available in the UI. Default is FALSE, meaning the segment will not be available in the UI, nor will the ID be available in the aw_get_segments function call.
debug	This enables the api call information to show in the console for help with debugging issues. default is FALSE
rsid	Adobe report suite ID (RSID). If an environment variable called AW_REPORTSUITE_ID exists in .Renviron or elsewhere and no rsid argument is provided, then the AW_REPORTSUITE_ID value will be used. Use <a href="#">aw_get_reportsuites()</a> to get a list of available rsid values.
company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renviron or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me()</a> to get a list of available company_id values.

## Details

See more information [here](#)

## Value

If the "create\_cm" argument is set to FALSE a list object definition will be returned. If the "create\_cm" argument is set to TRUE and the calculated metric is valid it will return a data frame of the newly created calculated metric id along with some other basic meta data. If it returns an error then the error response will be returned to help understand what needs to be corrected.

---

cm\_copy

*Copy a Calculated Metric*

---

## Description

This function copies an existing function and creates a duplicate based on the definition.

## Usage

```
cm_copy(
  id,
  name = NULL,
  description = NULL,
  polarity = NULL,
```



```

precision = NULL,
type = NULL,
create_cm = FALSE,
debug = FALSE,
rsid = NULL,
company_id = Sys.getenv("AW_COMPANY_ID")
)

```

## Arguments

id	The id of the old calculated metric
name	This is the name of the new calculated metric. If not provided, the prefix "Copy_" will be added to the existing name. (optional)
description	This is the description of the segment (optional)
polarity	Also known as 'Show Upward Trend As' in the UI. Options include 'positive' or 'negative'. Default is based on original calculated metric definition. This metric polarity setting shows whether Analytics should consider an upward trend in the metric as good (green) or bad (red). As a result, the report's graph will show as green or red when it's going up. Default is based on original calculated metric definition.
precision	Shows how many decimal places will be shown in the report. The maximum number of decimal places you can specify is 10. Also known as 'Decimal Places' in the UI. Default is based on original calculated metric definition.
type	Choices include decimal (default), time, percent, and currency. Also known as 'Format' in the UI. Default is based on original calculated metric definition.
create_cm	Used to determine if the segment should be created in the report suite or if the definition should be returned to be validated using cm_validate. Default is FALSE
debug	This enables the api call information to show in the console for help with debugging issues. default is FALSE
rsid	Adobe report suite ID (RSID). If an environment variable called AW_REPORTSUITE_ID exists in .Renvirom or elsewhere and no rsid argument is provided, then the AW_REPORTSUITE_ID value will be used. Use <a href="#">aw_get_reportsuites()</a> to get a list of available rsid values.
company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renvirom or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me()</a> to get a list of available company_id values.

## Details

See more information [here](#)

## Value

If the "create\_cm" argument is set to FALSE a list object definition will be returned. If the "create\_cm" argument is set to TRUE and the calculated metric is valid it will return a data frame of the

newly created calculated metric id along with some other basic meta data. If it returns an error then the error response will be returned to help understand what needs to be corrected.

---

 cm\_delete

*Delete A Calculated Metric Function*


---

## Description

Use this function to delete a specific calculated metric.

## Usage

```
cm_delete(
  id = NULL,
  warn = TRUE,
  locale = "en_US",
  debug = FALSE,
  rsid = Sys.getenv("AW_REPORTSUITE_ID"),
  company_id = Sys.getenv("AW_COMPANY_ID")
)
```

## Arguments

id	Calculated Metric ID to be deleted.
warn	Boolean of whether or not to include a warning message.
locale	language - default 'en_US'
debug	Default FALSE. Set this to TRUE to see the information about the api calls as they happen.
rsid	Adobe report suite ID (RSID). If an environment variable called AW_REPORTSUITE_ID exists in .Renvirom or elsewhere and no rsid argument is provided, then the AW_REPORTSUITE_ID value will be used. Use <a href="#">aw_get_reportsuites()</a> to get a list of available rsid values.
company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renvirom or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me()</a> to get a list of available company_id values.

## Value

A string confirming the calculated metric is deleted

---

cm_formula	<i>Create A Calculated Metric Formula</i>
------------	---

---

**Description**

Returns a JSON string formula to be used to build a calculated (derived) metric.

**Usage**

```
cm_formula(
  operator = c("divide", "multiply", "subtract", "add"),
  metrics = c("visits", "singlepagevisits"),
  seg_filters = NA,
  rsid = Sys.getenv("AW_REPORTSUITE_ID"),
  company_id = Sys.getenv("AW_COMPANY_ID")
)
```

**Arguments**

operator	Formula operators are divide (default), multiply, subtract, or add.
metrics	The one or two metrics in a formula calculation
seg_filters	A vector of segment filters to be added to a metric in the formula
rsid	Adobe report suite ID (RSID). If an environment variable called AW_REPORTSUITE_ID exists in .Renvirom or elsewhere and no rsid argument is provided, then the AW_REPORTSUITE_ID value will be used. Use <a href="#">aw_get_reportsuites()</a> to get a list of available rsid values.
company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renvirom or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me()</a> to get a list of available company_id values.

**Value**

A JSON string formula to be used in a calculated metric

---

cm_function	<i>Create A Calculated Metric Function</i>
-------------	--

---

**Description**

Returns a JSON string defining a function to be used to build a calculated (derived) metric.

**Usage**

```
cm_function(
  func = "col-sum",
  metric = "visits",
  dimension = NULL,
  seg_filter = NULL,
  rsid = Sys.getenv("AW_REPORTSUITE_ID"),
  company_id = Sys.getenv("AW_COMPANY_ID")
)
```

**Arguments**

func	Calculated function id. Only Basic single metric functions are able to be used.
metric	The metric to be used in the functional metric calculation. Default is visits
dimension	The dimension to be used in the functional metric calculation. Default is NULL
seg_filter	A segment filter to be added to a metric in the formula
rsid	Adobe report suite ID (RSID). If an environment variable called AW_REPORTSUITE_ID exists in .Renvirom or elsewhere and no rsid argument is provided, then the AW_REPORTSUITE_ID value will be used. Use <a href="#">aw_get_reportsuites()</a> to get a list of available rsid values.
company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renvirom or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me()</a> to get a list of available company_id values.

**Value**

Returns a full list of calculated metric functions or a specified function that the user can access.

---

cm_update	<i>Update Calculated Metric Functions</i>
-----------	---

---

**Description**

Update a specific calculated metric.

**Usage**

```
cm_update(
  id = NULL,
  updates = NULL,
  locale = "en_US",
  debug = FALSE,
  company_id = Sys.getenv("AW_COMPANY_ID")
)
```

**Arguments**

id	Returns details around a single calculated metric function if you specify the id. You can obtain the desired id by not including an ID value and finding the function in the results.
updates	List of changes or entire JSON definition object.
locale	All calculated metrics endpoints support the URL query parameter locale. Supported values are en_US, fr_FR, ja_JP, de_DE, es_ES, ko_KR, pt_BR, zh_CN, and zh_TW. This argument specifies which language is to be used for localized sections of responses.
debug	Set to TRUE to publish the full JSON request(s) being sent to the API to the console when the function is called. The default is FALSE.
company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renvi ron or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me()</a> to get a list of available company_id values.

**Value**

Returns a json string of information about the updated calculated metric

---

cm\_val

*Validate the definition of a Calculated Metric*


---

**Description**

This function checks if a calculated metric JSON string is valid

**Usage**

```
cm_val(
  definition = NULL,
  locale = "en_US",
  migrating = FALSE,
  debug = FALSE,
  rsid = Sys.getenv("AW_REPORTSUITE_ID"),
  company_id = Sys.getenv("AW_COMPANY_ID")
)
```

**Arguments**

definition	json string definition of a calculated metric
locale	The location of the language. en-US is default.
migrating	Include migration functions in validation. FALSE is default.
debug	This enables the api call information to show in the console for help with debugging issues. default is FALSE

rsid	Adobe report suite ID (RSID). If an environment variable called AW_REPORTSUITE_ID exists in .Renvirom or elsewhere and no rsid argument is provided, then the AW_REPORTSUITE_ID value will be used. Use <a href="#">aw_get_reportsuites()</a> to get a list of available rsid values.
company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renvirom or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me()</a> to get a list of available company_id values.

**Details**

See more information [here](#)

**Value**

A string confirming the calculated metric is valid or is not valid.

---

get\_cm\_functions      *Get Calculated Metric Functions*

---

**Description**

Returns a full list of calculated metric functions that the user can access.

**Usage**

```
get_cm_functions(
  id = NULL,
  debug = FALSE,
  company_id = Sys.getenv("AW_COMPANY_ID")
)
```

**Arguments**

id	Returns details around a single calculated metric function if you specify the id. You can obtain the desired id by not including an ID value and finding the function in the results.
debug	Set to TRUE to publish the full JSON request(s) being sent to the API to the console when the function is called. The default is FALSE.
company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renvirom or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me()</a> to get a list of available company_id values.

**Value**

Returns a full list of calculated metric functions or a specified function that the user can access.

---

get_me	<i>Get Company Ids</i>
--------	------------------------

---

**Description**

This function will quickly pull the list of company ids that you have access to.

**Usage**

```
get_me(req_path = "discovery/me")
```

**Arguments**

req\_path            The endpoint for that particular report

**Value**

A data frame of company ids and company names

**Examples**

```
## Not run:  
get_me()  
  
## End(Not run)
```

---

get_usage_logs	<i>Get a list of user usage</i>
----------------	---------------------------------

---

**Description**

This function returns the usage and access logs for a given date range within a 3 month period. The user must have Admin Console / Logs permissions (must be able to view the **Usage & Access Log** data in the web interface) in order to use this function.

**Usage**

```
get_usage_logs(  
  startDate = Sys.Date() - 91,  
  endDate = Sys.Date() - 1,  
  login = NULL,  
  ip = NULL,  
  rsid = NULL,  
  eventType = NULL,  
  event = NULL,  
  limit = 100,
```

```

    page = 0,
    debug = FALSE,
    company_id = Sys.getenv("AW_COMPANY_ID")
)

```

### Arguments

startDate	Start date for the maximum of a 3 month period.
endDate	End date for the maximum of a 3 month period.
login	The login value of the user you want to filter logs by.
ip	The IP address you want to filter logs by.
rsid	The report suite ID you want to filter logs by.
eventType	The numeric id for the event type you want to filter logs by. Leaving this blank returns all events. See the <a href="#">Usage Logs API Guide</a> for a complete list of event types.
event	The event description you want to filter logs by. No wildcards are permitted.
limit	The number of results to return per page. This argument works in conjunction with the page argument. The default is 10.
page	The "page" of results to display. This works in conjunction with the limit argument and is zero-based. For instance, if limit = 20 and page = 1, the results returned would be 21 through 40.
debug	Include the output and input of the api call in the console for debugging. Default is FALSE
company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renvi ron or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me</a> to get a list of available company_id values.

### Value

A data frame of logged events and the event meta data.

### Examples

```

## Not run:
get_usage_logs(startDate = Sys.Date()-91, endDate = Sys.Date()-1, limit = 100, page = 0)

## End(Not run)

```



---

get_users	<i>Get list of users</i>
-----------	--------------------------

---

**Description**

Retrieves a list of all users for the company designated by the auth token.

**Usage**

```
get_users(company_id = Sys.getenv("AW_COMPANY_ID"), limit = 10, page = 0)
```

**Arguments**

company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renvi ron or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me</a> to get a list of available company_id values.
limit	The number of results to return per page. This argument works in conjunction with the page argument. The default is 10.
page	The "page" of results to display. This works in conjunction with the limit argument and is zero-based. For instance, if limit = 20 and page = 1, the results returned would be 21 through 40.

**Value**

A data frame of users and their meta data.

**Examples**

```
## Not run:  
get_users(limit = 10, page = 0)  
  
## End(Not run)
```

---

proj_build	<i>Create a project in Adobe</i>
------------	----------------------------------

---

**Description**

Creates a new project in Adobe. Note: very early in development

**Usage**

```
proj_build(
  body = NULL,
  expansion = NULL,
  locale = "en_US",
  debug = FALSE,
  company_id = Sys.getenv("AW_COMPANY_ID")
)
```

**Arguments**

body	The project json string which include the configuration and definition
expansion	Comma-delimited list of additional project metadata fields to include on response. Available values : reportSuiteName, shares, tags, accessLevel, modified, externalReferences, definition
locale	Locale Default value : en_US
debug	Set to TRUE to publish the full JSON request(s) being sent to the API to the console when the function is called. The default is FALSE.
company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renvi ron or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me()</a> to get a list of available company_id values.

**Value**

A json string

---

proj\_update

*Edit a project in Adobe*

---

**Description**

Edits an existing project in Adobe. Note: very early in development

**Usage**

```
proj_update(
  projectId = NULL,
  body = NULL,
  expansion = NULL,
  locale = "en_US",
  debug = FALSE,
  company_id = Sys.getenv("AW_COMPANY_ID")
)
```

**Arguments**

projectId	The project id to be edited
body	The json string in list format which includes the edits to be made
expansion	Comma-delimited list of additional project metadata fields to include on response. Available values : reportSuiteName, shares, tags, accessLevel, modified, externalReferences, definition
locale	Locale Default value : en_US
debug	Set to TRUE to publish the full JSON request(s) being sent to the API to the console when the function is called. The default is FALSE.
company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renvi ron or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me()</a> to get a list of available company_id values.

**Value**

A json string

---

seg_build	<i>Build the Segment in Adobe Analytics</i>
-----------	---

---

**Description**

This function combines rules, containers and/or sequences into a single JSON string and can then make the post call to create the segment in Adobe Analytics or return the json string for use in other api calls or for validation.

**Usage**

```
seg_build(
  name = NULL,
  description = NULL,
  containers = NULL,
  rules = NULL,
  sequences = NULL,
  context = "hits",
  conjunction = "and",
  sequence = "in_order",
  sequence_context = "hits",
  exclude = FALSE,
  create_seg = FALSE,
  tagNames = NULL,
  internal = FALSE,
  debug = FALSE,
  rsid = Sys.getenv("AW_REPORTSUITE_ID"),
  company_id = Sys.getenv("AW_COMPANY_ID")
)
```

**Arguments**

name	This is the name of the new segment (required)
description	This is the description of the segment (required)
containers	List of the container(s) that make up the segment. Containers are list objects created using the <a href="#">seg_con()</a> function.
rules	List of the rule(s) to create a segment. Rules are list objects created using the <a href="#">seg_rule()</a> function.
sequences	List of the rule(s) and sequence container(s) that are combined to make a segment. Sequence containers are list objects created using the <a href="#">seg_seq()</a> function.
context	Defines the level that the segment logic should operate on. Valid values are visitors, visits, and hits. See Details
conjunction	This will tell how the different containers and rules should be compared. Use either 'and' or 'or'.
sequence	Used to define if the segment should be 'in_order' (default), 'after', or 'before' the sequence of events
sequence_context	Used to define the sequential items context which should be below the container context. ex. if container context is visitors then the sequence_context should be visits or hits
exclude	Excludes the main container which will include all rules. Only used when the rule arguments are used.
create_seg	Used to determine if the segment should be created in the report suite or if the definition should be returned to be used in a freeform table API call. Default is FALSE
tagNames	Apply tag names to the newly created calculated metric. Single string or a vector.
internal	Determines if this segment is to be available in the UI. Default is FALSE, meaning the segment will not be available in the UI, nor will the ID be available in the <a href="#">aw_get_segments</a> function call.
debug	This enables the api call information to show in the console for help with debugging issues. default is FALSE
rsid	Adobe report suite ID (RSID). If an environment variable called AW_REPORTSUITE_ID exists in .Renviron or elsewhere and no rsid argument is provided, then the AW_REPORTSUITE_ID value will be used. Use <a href="#">aw_get_reportsuites()</a> to get a list of available rsid values.
company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renviron or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me()</a> to get a list of available company_id values.

**Details****Context**

The rules in a segment have a context that specify the level of operation. The context can be "visitors", "visits" or "hits." As an example, let's build a segment rule where revenue is greater than 0 (meaning a purchase took place) and change the context to see how things change. If the context is set to "visitors", the segment includes all hits from visitors that have a purchase of some kind during a visit. This is useful in analyzing customer behavior in visits leading up to a purchase and possibly behavior after a purchase. If the context is set to "visits", the segment includes all hits from visits where a purchase occurred. This is useful for seeing the behavior of a visitor in immediate page views leading up to the purchase. If the context is set to "hits", the segment only includes hits where a purchase occurred, and no other hits. This is useful in seeing which products were most popular. In the above example, the context for the container listed is hits. This means that the container only evaluates data at the hit level, (in contrast to visit or visitor level). The rows in the container are also at the hit level.

### Value

If the "create\_seg" argument is set to FALSE a JSON string definition will be returned. If the "create\_seg" argument is set to TRUE and the segment is valid it will return a data frame of the newly created segment id along with some other basic meta data. If it returns an error then the error response will be returned to help understand what needs to be corrected.

---

seg_con	<i>Create the segment container</i>
---------	-------------------------------------

---

### Description

This function combines rules into a container.

### Usage

```
seg_con(context = "hits", conjunction = "and", rules = NULL, exclude = FALSE)
```

### Arguments

context	Defines the level that the segment logic should operate on. Valid values are visitors, visits, and hits. See Details
conjunction	This defines the relationship of the rules. And (default) and or are the two options.
rules	List of rules and/or containers. Must be wrapped in a list() function. Adding a container list item will nest it within a container.
exclude	Exclude the entire container

## Details

### Context

The rules in a segment have a context that specify the level of operation. The context can be "visitors", "visits" or "hits." As an example, let's build a segment rule where revenue is greater than 0 (meaning a purchase took place) and change the context to see how things change. If the context is set to "visitors", the segment includes all hits from visitors that have a purchase of some kind during a visit. This is useful in analyzing customer behavior in visits leading up to a purchase and possibly behavior after a purchase. If the context is set to "visits", the segment includes all hits from visits where a purchase occurred. This is useful for seeing the behavior of a visitor in immediate page views leading up to the purchase. If the context is set to "hit", the segment only includes hits where a purchase occurred, and no other hits. This is useful in seeing which products were most popular. In the above example, the context for the container listed is hits. This means that the container only evaluates data at the hit level, (in contrast to visit or visitor level). The rules in the container are also at the hit level.

### Value

a structured list of containers to be used to build the segment

---

seg\_copy

*Copy a segment in Adobe Analytics*

---

### Description

This function copies an existing function and creates a duplicate based on the definition.

### Usage

```
seg_copy(
  id,
  name = NULL,
  description = NULL,
  polarity = NULL,
  precision = NULL,
  type = NULL,
  create_seg = FALSE,
  debug = FALSE,
  rsid = NULL,
  company_id = Sys.getenv("AW_COMPANY_ID")
)
```

### Arguments

id	The id of the old segment
name	This is the name of the new segment. If not provided, the prefix "Copy_" will be added to the existing name. (optional)

description	This is the description of the segment (optional)
polarity	Also known as 'Show Upward Trend As' in the UI. Options include 'positive' or 'negative'. Default is based on original segment definition. This metric polarity setting shows whether Analytics should consider an upward trend in the metric as good (green) or bad (red). As a result, the report's graph will show as green or red when it's going up. Default is based on original segment definition.
precision	Shows how many decimal places will be shown in the report. The maximum number of decimal places you can specify is 10. Also known as 'Decimal Places' in the UI. Default is based on original segment definition.
type	Choices include decimal (default), time, percent, and currency. Also known as 'Format' in the UI. Default is based on original segment definition.
create_seg	Used to determine if the segment should be created in the report suite or if the definition should be returned to be validated using seg_val. Default is FALSE
debug	This enables the api call information to show in the console for help with debugging issues. default is FALSE
rsid	Adobe report suite ID (RSID). If an environment variable called AW_REPORTSUITE_ID exists in .Renvi ron or elsewhere and no rsid argument is provided, then the AW_REPORTSUITE_ID value will be used. Use <a href="#">aw_get_reportsuites()</a> to get a list of available rsid values.
company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renvi ron or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me()</a> to get a list of available company_id values.

## Details

See more information [here](#)

## Value

If the "create\_seg" argument is set to FALSE a list object definition will be returned. If the "create\_seg" argument is set to TRUE and the segment is valid it will return a data frame of the newly created segment id along with some other basic meta data. If it returns an error then the error response will be returned to help understand what needs to be corrected.

---

seg\_delete

*Delete A Segment*

---

## Description

Use this function to delete a specific segment in Adobe Analytics

**Usage**

```

seg_delete(
  id = NULL,
  warn = TRUE,
  locale = "en_US",
  debug = FALSE,
  rsid = Sys.getenv("AW_REPORTSUITE_ID"),
  company_id = Sys.getenv("AW_COMPANY_ID")
)

```

**Arguments**

id	Segment ID to be deleted.
warn	Boolean of whether or not to include a warning message.
locale	language - default 'en_US'
debug	Default FALSE. Set this to TRUE to see the information about the api calls as they happen.
rsid	Adobe report suite ID (RSID). If an environment variable called AW_REPORTSUITE_ID exists in .Renvirom or elsewhere and no rsid argument is provided, then the AW_REPORTSUITE_ID value will be used. Use <a href="#">aw_get_reportsuites()</a> to get a list of available rsid values.
company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renvirom or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me()</a> to get a list of available company_id values.

**Value**

A string confirming the segment has or has not been deleted

---

seg_rule	<i>Create the segment rule</i>
----------	--------------------------------

---

**Description**

This function creates the simple rule of a segment.

**Usage**

```

seg_rule(
  dimension = NULL,
  metric = NULL,
  verb = NULL,
  object = NULL,
  description = NULL,
  is_distinct = FALSE,

```



```

    attribution = "repeating",
    attribution_context = "visitors",
    validate = FALSE,
    rsid = Sys.getenv("AW_REPORTSUITE_ID"),
    company_id = Sys.getenv("AW_COMPANY_ID")
)

```

## Arguments

dimension	This is the subject of the rule. The value should be the dimension id. Only the dimension or metric can be used at a time.
metric	This is the subject of the rule. The value should be the metric id. Only the dimension or metric can be used at a time.
verb	Choose from any of the 30 different verbs. Use the <a href="#">seg_verbs</a> package data to see all available verbs along with the descriptions.
object	This is the object of the rule and answers the question what or how many
description	The internal description for the rule. (optional) This will not show in the UI but could be very helpful when using the API.
is_distinct	This will segment on a distinct count of items within a dimension. Examples: "Visitors who viewed more than 5 distinct products," or "Visits where more than 5 distinct pages were seen."
attribution	Define the type of attribution. Either repeating (default), instance, or nonrepeating. See Details for more information.
attribution_context	When applying a non-repeating instance attribution model to a rule the context for the attribution must be visitors (default) or visits
validate	Set to TRUE when metric or dimension validation is preferred. Default is FALSE. Validation will slow down the function response time but ensure a valid rule result.
rsid	Adobe report suite ID (RSID). If an environment variable called AW_REPORTSUITE_ID exists in .Renviron or elsewhere and no rsid argument is provided, then the AW_REPORTSUITE_ID value will be used. Use <a href="#">aw_get_reportsuites()</a> to get a list of available rsid values.
company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renviron or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me()</a> to get a list of available company_id values.

## Details

**Attribution Models** Available for dimensions only, these models determine what values in a dimension to segment for. Dimension models are particularly useful in sequential segmentation.

- *repeating* (default): Includes instances and persisted values for the dimension.
- *instance*: Includes instances for the dimension.
- *nonrepeating* instance: Includes unique instances (non-repeating) for the dimension. This is the model applied in Flow when repeat instances are excluded.

**Value**

A structured list defining the rule for a segment

---

seg_seq	<i>Create the segment sequence container</i>
---------	--

---

**Description**

This function combines rules into a sequence container.

**Usage**

```
seg_seq(
  context = "visits",
  rules = NULL,
  sequence = "in_order",
  exclude = FALSE,
  exclude_checkpoint = NULL
)
```

**Arguments**

context	Defines the level that the segment logic should operate on. Valid values for sequential segments is visitors and visits. See Details
rules	List of rules created using <a href="#">seg_rule()</a> function. Must be wrapped in a list() function.
sequence	How should the sequence of items be considered. Options: in_order (default), before, after, and, or
exclude	Excludes the entire sequence container which will include all rules.
exclude_checkpoint	Which checkpoints (rules) should be excluded. Example c(1, 4). See Details

**Details****Context**

The rules in a segment have a context that specify the level of operation. The context can be "visitors", "visits" or "hits." As an example, let's build a segment rule where revenue is greater than 0 (meaning a purchase took place) and change the context to see how things change. If the context is set to "visitors", the segment includes all hits from visitors that have a purchase of some kind during a visit. This is useful in analyzing customer behavior in visits leading up to a purchase and possibly behavior after a purchase. If the context is set to "visits", the segment includes all hits from visits where a purchase occurred. This is useful for seeing the behavior of a visitor in immediate page views leading up to the purchase. If the context is set to "hits", the segment only includes hits where a purchase occurred, and no other hits. This is useful in seeing which products were most popular. In the above example, the context for the container listed is hits. This means that the

container only evaluates data at the hit level, (in contrast to visit or visitor level). The rows in the container are also at the hit level.

### Exclude checkpoint

Ensures the next checkpoint doesn't happen between the preceding checkpoint and the subsequent checkpoint. If there is no subsequent checkpoint then the excluded checkpoint must not occur at any point after the preceding checkpoint. If there is no preceding checkpoint then the excluded checkpoint must not have occurred at any point preceding the subsequent checkpoint.

### More Information

Sequential segments can be difficult to get right. Referencing this article can help: <https://experienceleague.adobe.com/docs/workflow/seg-sequential-build.html?lang=en>

## Value

a structured list of containers to be used to build the segment

---

seg_then	<i>Create the segment sequence then object</i>
----------	--

---

## Description

This function creates a then list object which restricts the time constraint of a segment to be added to a sequence segment.

## Usage

```
seg_then(limit = "within", count = 1, unit = "year")
```

## Arguments

limit	The limitation of the restriction. Either within (default) or after
count	How many of the units should be used. 1 is set as default.
unit	A unit of time. Valid values are hit, visit, minute, hour, day, week (default), month, quarter, or year. Always use the singular form.

## Details

### Combining seg\_then arguments:

In the UI you can add 'after' and 'within' statements to create a more complex time restriction. The same can be accomplished using this function by listing the limits, counts, and units in a c() function. This would look like: `limit = c('within', 'after'), count = c(5, 1), unit = c('hit', 'visit')`

### Using within and after in the same time seg\_then function call:

Time restrictions can only be combined using 'within' first before 'after'. The function will automatically align these to be in the correct list item order.

### A word about unit values:

Currently pageviews and dimensions are not supported unit values.

**Value**

a structured list of time restrictions to be used to build the sequential segment

---

 seg\_update
 

---

*Update A Segment*


---

**Description**

Update a specific segment

**Usage**

```
seg_update(
  id = NULL,
  updates = NULL,
  locale = "en_US",
  debug = FALSE,
  company_id = Sys.getenv("AW_COMPANY_ID")
)
```

**Arguments**

id	The id of the segment you are wanting to update
updates	List of changes or entire definition object as a list object.
locale	The URL query parameter locale. Supported values are en_US, fr_FR, ja_JP, de_DE, es_ES, ko_KR, pt_BR, zh_CN, and zh_TW. This argument specifies which language is to be used for localized sections of responses.
debug	Set to TRUE to publish the full JSON request(s) being sent to the API to the console when the function is called. The default is FALSE.
company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in <code>.Renvi ron</code> or elsewhere and no <code>company_id</code> argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me()</a> to get a list of available <code>company_id</code> values.

**Value**

json string of updated segment information

---

seg_val	<i>Validate a segment</i>
---------	---------------------------

---

### Description

Returns a segment validation response for a segment contained in a json string object.

### Usage

```
seg_val(
  segment_body = NULL,
  rsid = Sys.getenv("AW_REPORTSUITE_ID"),
  debug = FALSE,
  company_id = Sys.getenv("AW_COMPANY_ID")
)
```

### Arguments

segment_body	The json string of the segment that is being validated (required)
rsid	Adobe report suite ID (RSID). If an environment variable called AW_REPORTSUITE_ID exists in .Renviron or elsewhere and no rsid argument is provided, then the AW_REPORTSUITE_ID value will be used. Use <a href="#">aw_get_reportsuites()</a> to get a list of available rsid values.
debug	This enables the api call information to show in the console for help with debugging issues. default is FALSE
company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renviron or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me()</a> to get a list of available company_id values.

### Value

If the segment is valid a message saying the segment validates is returned. If the segment doesn't validate the errors are returned in a data frame.

---

seg_verbs	<i>Verbs available in segment rules.</i>
-----------	--

---

### Description

A dataset containing the list of available verbs to be used in segment rules.

### Usage

```
seg_verbs
```

**Format**

A data frame with 34 rows and 5 variables:

**type** one of number, string, or exists

**class** gives the context of the type of value is expected, either string, list, glob, number, or exists

**verb** the actual verb id to be used in the segment definition

**description** a simple description of the verb

**arg** specifies what argument to use when building the segment verb function ...

**Source**

<https://developer.adobe.com/analytics-apis/docs/2.0/guides/endpoints/segments/definition/#available-data-comparison-functions>

---

tags\_add

*Add a tag to a component*

---

**Description**

Enables the creation of a new tag and applies the new tag to the passed component

**Usage**

```
tags_add(
  company_id = Sys.getenv("AW_COMPANY_ID"),
  componentId = NULL,
  componentType = NULL,
  tagNames = NULL,
  overwrite = FALSE,
  debug = FALSE
)
```

**Arguments**

company_id	Company ID. If an environment variable called AW_COMPANY_ID exists in .Renvi ron or elsewhere and no company_id argument is provided, then the AW_COMPANY_ID value will be used. Use <a href="#">get_me</a> to get a list of available company_id values.
componentId	The component id being requested. Default is NULL
componentType	The component type being requested. Options include segment, dashboard, bookmark, calculatedMetric, project, dateRange, metric, dimension, virtualReportSuite, scheduledJob, alert, classification. Default is NULL
tagNames	Comma separated vector of tag names.
overwrite	Overwrite the existing tag names on a component. To append a new tag name use FALSE (default). To overwrite the existing tags on a component use TRUE.
debug	Include the output and input of the api call in the console for debugging. Default is FALSE

*tags\_add*

47

**Value**

A data frame of segments and their meta data.

# Index

- \* **auth**
  - aw\_auth, 4
- \* **datasets**
  - seg\_verbs, 45
- \* **options**
  - aw\_auth\_with, 5

auth\_jwt (aw\_auth), 4  
auth\_oauth (aw\_auth), 4  
auth\_s2s (aw\_auth), 4  
aw\_anomaly\_report, 3  
aw\_auth, 4  
aw\_auth(), 6, 22  
aw\_auth\_name (aw\_auth\_with), 5  
aw\_auth\_path (aw\_auth\_with), 5  
aw\_auth\_with, 5  
aw\_auth\_with(), 5  
aw\_freeform\_table, 6  
aw\_freeform\_table(), 21  
aw\_get\_calculatedmetrics, 10, 15  
aw\_get\_calculatedmetrics(), 7, 10  
aw\_get\_dimensions, 12  
aw\_get\_dimensions(), 7, 10  
aw\_get\_metrics, 12, 14  
aw\_get\_metrics(), 7, 10  
aw\_get\_project\_config, 16  
aw\_get\_projects, 15  
aw\_get\_reportsuites, 11, 13, 14, 17, 18  
aw\_get\_reportsuites(), 7, 10, 24–28, 30, 36, 39–41, 45  
aw\_get\_segments, 18  
aw\_get\_segments(), 7, 10  
aw\_get\_tags, 19  
aw\_segment\_table, 20  
aw\_segment\_table(), 10  
aw\_token, 22  
aw\_workspace\_report, 22

cm\_build, 23  
cm\_copy, 24  
cm\_delete, 26  
cm\_formula, 27  
cm\_formula(), 23  
cm\_function, 27  
cm\_update, 28  
cm\_val, 29

get\_cm\_functions, 30  
get\_me, 10, 13, 14, 17, 18, 20, 31, 32, 33, 46  
get\_me(), 7, 10, 16, 24–30, 34–36, 39–41, 44, 45  
get\_usage\_logs, 31  
get\_users, 33

proj\_build, 33  
proj\_update, 34

seg\_build, 35  
seg\_con, 37  
seg\_con(), 36  
seg\_copy, 38  
seg\_delete, 39  
seg\_rule, 40  
seg\_rule(), 36, 42  
seg\_seq, 42  
seg\_seq(), 36  
seg\_then, 43  
seg\_update, 44  
seg\_val, 45  
seg\_verbs, 41, 45

tags\_add, 46  
tibble::tibble(), 21