

Package ‘hwig’

October 13, 2022

Title Half-Weight Index Gregariousness

Version 0.0.2

Description The half-weight index gregariousness (HWIG) is an association index used in social network analyses. It extends the half-weight association index (HWI), correcting for level of gregariousness in individuals. It is calculated using group by individual data according to methods described in Godde et al. (2013) <[doi:10.1016/j.anbehav.2012.12.010](https://doi.org/10.1016/j.anbehav.2012.12.010)>.

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.1.2

Depends R (>= 2.10)

Imports asnipe, spatsock, data.table

Suggests testthat

BugReports <https://github.com/robitallec/hwig/issues>

URL <https://gitlab.com/robit.a/hwig>, <https://github.com/robitallec/hwig>

NeedsCompilation no

Author Alec L. Robitaille [aut, cre] (<<https://orcid.org/0000-0002-4706-1762>>)

Maintainer Alec L. Robitaille <robit.alec@gmail.com>

Repository CRAN

Date/Publication 2021-09-30 11:50:09 UTC

R topics documented:

calc_hwi	2
calc_hwig	3
DT	4
get_names	4

Index	6
--------------	----------

`calc_hwi`*Calculate HWI*

Description

Calculates the Half-Weight Association Index

Usage

```
calc_hwi(DT, id, group, by = NULL)
```

Arguments

<code>DT</code>	input group membership data, in individual/group format
<code>id</code>	column indicating id in DT
<code>group</code>	column indicating group in DT
<code>by</code>	column(s) to split calculation by. e.g.: year

Details

Expects an input 'DT' with id and group column, e.g. as returned by [group_pts](#).

Value

HWI data.table or list of data.tables.

See Also

[calc_hwig](#)

Examples

```
# Load data.table
library(data.table)

# Load example data
DT <- fread(system.file("extdata", "DT.csv", package = "hwi"))

# Calculate HWI
hwi <- calc_hwi(DT, 'id', 'group', 'yr')
```

`calc_hwig`*Calculate HWIG*

Description

Calculates the Half-Weight Association Index according to the method described in Godde et al. (2013).

Usage

```
calc_hwig(hwi)
```

Arguments

`hwi` output of `calc_hwi`. Either a `data.table` or a list of `data.tables`. See Details.

Details

It is expected that the input `'hwi'` is the output from `'calc_hwi'`. If `'by'` was provided in that function, `'hwi'` will be a list of `data.tables`. Alternatively if `'by'` wasn't provided, `'hwi'` will be a single `data.table`.

Value

HWIG `data.table` or list of `data.tables`.

References

Sophie Godde, Lionel Humbert, Steeve D. Côté, Denis Réale, Hal Whitehead. Correcting for the impact of gregariousness in social network analyses. *Animal Behaviour*. Volume 85, Issue 3. 2013.

See Also

[calc_hwi get_names](#)

Examples

```
# Load data.table
library(data.table)

# Load example data
DT <- fread(system.file("extdata", "DT.csv", package = "hwig"))

# Calculate HWI
hwi <- calc_hwi(DT, 'id', 'group', 'yr')

# Calculate HWIG
hwig <- calc_hwig(hwi)
```

DT *Example data for input to 'hwig'*

Description

Example data for input to 'hwig'

Format

A data.table with 14297 rows and 3 variables:

ID individual identifier

year integer representing the year

Source

```
# Load packages library(spatSOC) library(data.table)
# Read example data DT <- fread(system.file("extdata", "DT.csv", package = "spatsoc"))
# Cast the character column to POSIXct DT[, datetime := as.POSIXct(datetime, tz = 'UTC')]
# Temporal grouping group_times(DT, datetime = 'datetime', threshold = '20 minutes')
# Spatial grouping with timegroup group_pts( DT, threshold = 5, id = 'ID', coords = c('X', 'Y'),
timegroup = 'timegroup' )
fwrite(DT[, .(id = ID, group, yr = year(datetime))], 'inst/extdata/DT.csv')
```

Examples

```
# Load data.table
library(data.table)

# Read example data
DT <- fread(system.file("extdata", "DT.csv", package = "hwig"))
```

get_names *Get HWI/HWIG names*

Description

Helper function, to return names of each matrix

Usage

```
get_names(DT, by)
```

Arguments

DT input group membership data, in individual/group format
by column(s) to split calculation by. e.g.: year

Value

names corresponding to values of by for each of the returned list of matrices in [calc_hwi](#) and [calc_hwig](#).

See Also

[calc_hwi](#) [calc_hwig](#)

Examples

```
# Load data.table
library(data.table)

# Load example data
DT <- fread(system.file("extdata", "DT.csv", package = "hwig"))

# Calculate HWI
hwi <- calc_hwi(DT, 'id', 'group', 'yr')

# Calculate HWIG
hwig <- calc_hwig(hwi)

# Set names
nms <- get_names(DT, 'yr')
names(hwig) <- nms
```

Index

`calc_hwi`, [2](#), [3](#), [5](#)
`calc_hwig`, [2](#), [3](#), [5](#)

`DT`, [4](#)

`get_names`, [3](#), [4](#)
`group_pts`, [2](#)