

Package ‘nplr’

October 13, 2022

Type Package

Title N-Parameter Logistic Regression

Version 0.1-7

Date 2016-12-25

Maintainer Frederic Commo <fredcommo@gmail.com>

Depends methods

Imports stats,graphics,utils

Suggests RUnit,knitr

VignetteBuilder knitr

Description Performing drug response analyses and IC50 estimations using n-Parameter logistic regression. Can also be applied to proliferation analyses.

License GPL

URL <https://github.com/fredcommo/nplr>

NeedsCompilation no

Author Frederic Commo [aut, cre],
Brian M. Bot [aut]

Repository CRAN

Date/Publication 2016-12-28 16:38:22

R topics documented:

convertToProp	2
getEstimates	3
nplr	5
nplrAccessors	8
overlay	8
plot.nplr	9
summary.nplr	11
Index	12

convertToProp *Function to Convert a Vector Into Proportions.*

Description

Convert a vector of values to proportions, given a minimum and a maximum value (optional). See Details and Examples.

Usage

```
convertToProp(y, T0 = NULL, Ctrl = NULL)
```

Arguments

`y` : a vector of values (responses to x).
`T0` : the minimal value to consider. If NULL (default), `min(y, na.rm=TRUE)` will be used. See Details and Warning.
`Ctrl` : the maximal value to consider. If NULL (default), `max(y, na.rm=TRUE)` will be used. See Details and Warning.

Details

In typical cell viability experiments, responses to drug concentrations (inhibition rate) may be estimated with respect to a time zero (T_0) and an untreated condition values (`Ctrl`), as described in [1]:

If none of the `T0` and `Ctrl` values are provided, `min(y, na.rm=TRUE)` and `max(y, na.rm=TRUE)` will be used, respectively. See Warning.

Value

a vector of values.

Warning: Note that, for drug response analyses, rescaling the responses between 0 to 1 using to the min and max of `y`, would lead to estimate a EC50 (the half effect between the maximum and the minimum of the observed effects), rather than a IC50.

Note

The data used as examples come from the NCI-60 Growth Inhibition Data: <https://wiki.nci.nih.gov/display/NCIDTPdata/NCI-60+Growth+Inhibition+Data>, except for multicell.tsv which are simulated data.

Author(s)

Frederic Commo, Brian M. Bot

References

1 - <https://dtp.nci.nih.gov/branches/btb/ivclsp.html>

See Also

[nplr](#)

Examples

```
## Using the MDA-N data
op <- par(no.readonly=TRUE)      # save default parameters

require(nplr)
path <- system.file("extdata", "mdan.txt", package = "nplr")
mdan <- read.delim(path)

# fit a model on the original responses (proportions of control):
conc <- mdan$CONC
y0 <- mdan$GIPROP
model0 <- nplr(conc, y0)

# Adjust the data between 0 to 1, then fit a new model:
y1 <- convertToProp(y0)
model1 <- nplr(conc, y1)

par(mfrow=c(1, 2))
plot(model0, ylim = range(0, 1), main = "Original y values")
plot(model1, ylim = range(0, 1), main = "Rescaled y values")
par(op)
```

getEstimates

Function to Estimate x Given y.

Description

This function takes as its first argument a model returned by `nplr()`. By inverting the logistic model, it estimates the x values corresponding to one (or a vector of) y target(s) provided. The standard error of the model, defined as the mean squared error on the fitted values, is used to estimate a confidence interval on the predicted x values, according to the specified `conf.level`. see Details.

Usage

```
## S4 method for signature 'nplr'
getEstimates(object, targets = seq(.9, .1, by = -.1), B = 1e4, conf.level = .95)
```

Arguments

object	: an object of class nplr.
targets	: one, or a vector of, numerical value(s) for which the corresponding x has to be estimated. Default are target values from .9 to .1.
B	: the length of the y distribution from which the x confidence interval is estimated.
conf.level	: the estimated x confidence interval, bounded by (1-conf.level)/2 and 1 - (1-conf.level)/2 (by default .95, which gives x.025 and x.975).

Details

In n-parameter logistic regressions, none of the parameters follow any particular distribution from which confidence intervals can be estimated. To overcome this issue, the standard error is used to generate a normal distribution of the target(s) passed to the function. The quantiles of that distribution are used in order to provide estimated bounds for the corresponding x value, with respect to conf.level. See also Warning.

Value

A data set containing:

y	: the target value.
x.05	: the lower bound of the estimated 95% confidence interval (default). If another value is passed to conf.level, x will be labelled as x.(1-conf.level)/2.
x	: the estimated value.
x.95	: the upper bound of the estimated 95% confidence interval (default). If another value is passed to conf.level, x will be labelled as x.1-(1-conf.level)/2.

Warning: Notice that, if any $target \leq B$ or $target \geq T$, in other words outside the 2 asymptotes, the maximal (or minimal) possible value the model can estimate is returned.

Note

The data used in the examples are samples from the NCI-60 Growth Inhibition Data: <https://wiki.nci.nih.gov/display/NCIDTPdata/NCI-60+Growth+Inhibition+Data>, except for multicell.tsv which are simulated data.

Author(s)

Frederic Commo, Brian M. Bot

See Also

[nplr](#), [plot.nplr](#), [nplrAccessors](#)

Examples

```
# Using the PC-3 data
require(nplr)
path <- system.file("extdata", "pc3.txt", package="nplr")
pc3 <- read.delim(path)
model <- nplr(x = pc3$CONC, y = pc3$GIPROP)
getEstimates(model)
getEstimates(model, c(.3, .6), conf.level = .9)
```

nplr

Function to Fit n-Parameter Logistic Regressions.

Description

This function computes a weighted n-parameters logistic regression, given x (typically compound concentrations) and y values (responses: optic densities, fluorescence, cell counts,...). See Details.

Usage

```
nplr(x, y, useLog = TRUE, LPweight = 0.25, npars = "all",
      method = c("res", "sdw", "gw"), silent = FALSE)
```

Arguments

x : a vector of numeric values, e.g. a vector of drug concentrations.

y : a vector of numeric values, e.g. a vector of responses, typically provided as proportions of control.

useLog : Logical. Should x-values be Log10-transformed. Default to TRUE, set to FALSE if x is already in Log10.

LPweight : a coefficient to adjust the weights. *LPweight* = 0 will compute a non-weighted np-logistic regression.

npars : a numeric value (or "all") to specify the number of parameters to use in the model. If "all" the logistic model will be tested with 2 to 5 parameters, and the best option will be returned. See Details

method : a character string to specify what weight method to use. Options are "res" (Default), "sdw", "gw". See Details

silent : Logical. Specify whether warnings ad/or messages has to be silenced. Default to FALSE.

Details

The 5-parameter logistic regression is of the form:

$$y = B + (T - B) / [1 + 10^{(b * (xmid - x))}]^s$$

where B and T are the bottom and top asymptotes, respectively, b and xmid are the Hill slope and the x-coordinate at the inflexion point, respectively, and s is an asymmetric coefficient. This equation is sometimes referred to as the Richards' equation [1,2].

When specifying `npars = 4`, the `s` parameter is forced to be 1, and the corresponding model is a 4-parameter logistic regression, symmetrical around its inflexion point. When specifying `npars = 3` or `npars = 2`, add 2 more constraints and force B and T to be 0 and 1, respectively.

Weight methods:

The model parameters are optimized, simultaneously, using `nlm`, given a sum of squared errors function, $sse(Y)$, to minimize:

$$sse(Y) = \sum[W.(Y_{obs} - Y_{fit})^2]$$

where `Yobs`, `Yfit` and `W` are the vectors of observed values, fitted values and weights, respectively.

In order to reduce the effect of possible outliers, the weights can be computed in different ways, specified in `nplr`:

- residual weights, "res":

$$W = (1/residuals)^{LPweight}$$

where `residuals` and `LPweight` are the squared error between the observed and fitted values, and a tuning parameter, respectively. Best results are generally obtained by setting `LPweight = 0.25` (default value), while setting `LPweight = 0` results in computing a non-weighted sum of squared errors.

- standard weights, "sdw":

$$W = 1/Var(Y_{obs_r})$$

where `Var(Yobs_r)` is the vector of the within-replicates variances.

- general weights, "gw":

$$W = 1/Y_{fit}^{LPweight}$$

where `Yfit` are the fitted values. As for the residuals-weights method, setting `LPweight = 0` results in computing a non-weighted sum of squared errors.

The standard weights and general weights methods are described in [3].

Value

An object of class `nplr`.

slots

- `x` : the x values as they are used in the model. It can be $\text{Log}_{10}(x)$ if `useLog` was set to `TRUE`.
- `y` : the y values.
- `useLog` : logical.
- `npars` : the best number of parameters if `npars="all"`, the specified number of parameters, otherwise.
- `LPweight` : the weights tuning parameter.

- yFit : the y fitted values.
- xCurve : the x values generated to draw the curve. 200 points between the min and max of x.
- yCurve : the fitted values used to draw the curve. the fitted values corresponding to xCurve.
- infPoint : the inflexion point x and y coordinates.
- goodness : the goodness-of-fit. The correlation between the fitted and the observed y values
- stdErr : the mean squared error between the fitted and the observed y values
- pars : the model parameters.
- AUC : the area under the curve estimated using both the trapezoid method and the Simpson's rule.

Note

The data used in the examples are samples from the NCI-60 Growth Inhibition Data: <https://wiki.nci.nih.gov/display/NCIDTPdata/NCI-60+Growth+Inhibition+Data>, except for multicell.tsv which are simulated data.

Author(s)

Frederic Commo, Brian M. Bot

References

- 1- Richards, F. J. (1959). A flexible growth function for empirical use. J Exp Bot 10, 290-300.
- 2- Giraldo J, Vivas NM, Vila E, Badia A. Assessing the (a)symmetry of concentration-effect curves: empirical versus mechanistic models. Pharmacol Ther. 2002 Jul;95(1):21-45.
- 3- Motulsky HJ, Brown RE. Detecting outliers when fitting data with nonlinear regression - a new method based on robust nonlinear regression and the false discovery rate. BMC Bioinformatics. 2006 Mar 9;7:123.

See Also

[convertToProp](#), [getEstimates](#), [plot.nplr](#), [nplrAccessors](#)

Examples

```
# Using the PC-3 data
require(nplr)
path <- system.file("extdata", "pc3.txt", package = "nplr")
pc3 <- read.delim(path)
model <- nplr(x = pc3$CONC, y = pc3$GIPROP)
plot(model)
```

nplrAccessors	nplr accessor functions
---------------	---

Description

Methods for extracting information from an object of class `nplr`. Each of the below methods are simply convenience functions which extract the corresponding slots (as the name of each method suggests) from the object of class `nplr`.

Methods

```
signature(object = "nplr") • getX(object)
  • getY(object)
  • getXcurve(object)
  • getYcurve(object)
  • getFitValues(object)
  • getInflexion(object)
  • getPar(object)
  • getAUC(object)
  • getGoodness(object)
  • getStdErr(object)
  • getWeights(object)
```

See Also

[nplr](#), [getEstimates](#)

overlay	<i>Plotting Multiple nplr Objects</i>
---------	---------------------------------------

Description

To superimpose multiple logistic models fitted using `nplr`.

Usage

```
overlay(modellist = NULL, showLegend = TRUE, cols = NULL, ...)
```

Arguments

<code>modellist</code>	: list. A list of objects of class <code>nplr</code> .
<code>showLegend</code>	: logical. Whether the legend has to be displayed.
<code>cols</code>	: character. A vector of colors to use. If NULL (default), greys will be used.
<code>...</code>	: Other graphical parameters. See par .

Details

None

Source

None

References

None

See Also

[plot.nplr](#)

Examples

```
path <- system.file("extdata", "multicell.tsv", package="nplr")
multicell <- read.delim(path)

# Computing models (to store in a list)
cellsList <- split(multicell, multicell$cell)
Models <- lapply(cellsList, function(tmp){
  nplr(tmp$conc, tmp$resp, silent = TRUE)
})

# Visualizing
overlay(Models, xlab = expression(Log[10](Conc.)), ylab = "Resp.",
  main="Superimposing multiple curves", cex.main=1.5)
```

plot.nplr

Plotting nplr Objects

Description

This function allows visualizing logistic models fitted using [nplr](#).

Usage

```
## S3 method for class 'nplr'
plot(x, pcol = "aquamarine1", lcol = "red3",
  showEstim = FALSE, showCI = TRUE, showGOF = TRUE, showInfl = FALSE,
  showPoints = TRUE, showSDerr = FALSE, B = 1e4, conf.level = .95, unit = "", ...)
```

Arguments

x	: an object of class <code>nplr</code>
pcol	: the points color.
lcol	: the line color.
showEstim	: logical/numeric. If a numerical value is passed (a y value to reach), the estimated x value, and interval, is displayed on the plot. Default is FALSE
showCI	: logical. show the estimated confidence interval
showGOF	: logical. show the estimated goodness-of-fit.
showInfl	: logical. add the inflexion point on the plot.
showPoints	: logical. add the points on the plot.
showSDerr	: logical. add the standard errors on the plot (maybe useful in case of experiment with replicates).
B	: the length of simulated y values. Used to estimate the confidence interval
conf.level	: the confidence level. See <code>getEstimates</code>
unit	: the unit to specify when <code>showEstim</code> is TRUE. Default is an empty string.
...	: other graphical parameters. See <code>par</code> .

Details

None

Note

The data used in the examples are samples from the NCI-60 Growth Inhibition Data: <https://wiki.nci.nih.gov/display/NCIDTPdata/NCI-60+Growth+Inhibition+Data>, except for multicell.tsv which are simulated data.

Source

None

References

None

See Also

[overlay](#)

Examples

```
# Using the PC-3 data
require(nplr)
path <- system.file("extdata", "pc3.txt", package = "nplr")
pc3 <- read.delim(path)
model <- nplr(x = pc3$CONC, y = pc3$GIPROP)
plot(model, showEstim = 0.5, unit = "nM")
```

summary.nplr	<i>summarizing nplr Objects</i>
--------------	---------------------------------

Description

A S3 method to visualize a model summary as a table.

Usage

```
## S3 method for class 'nplr'  
summary(object, ...)
```

Arguments

object : an object of class `nplr`
... : other optional parameters (not used).

Details

None

Note

The data used in the examples are samples from the NCI-60 Growth Inhibition Data: <https://wiki.nci.nih.gov/display/NCIDTPdata/NCI-60+Growth+Inhibition+Data>, except for multicell.tsv which are simulated data.

Source

None

References

None

See Also

[plot.nplr](#)

Examples

```
# Using the PC-3 data  
require(nplr)  
path <- system.file("extdata", "pc3.txt", package = "nplr")  
pc3 <- read.delim(path)  
model <- nplr(x = pc3$CONC, y = pc3$GIPROP)  
summary(model)
```

Index

- * **datasets**
 - overlay, 8
 - plot.nplr, 9
 - summary.nplr, 11
- convertToProp, 2, 7
- getAUC (nplrAccessors), 8
- getAUC, nplr-method (nplrAccessors), 8
- getAUC-methods (nplrAccessors), 8
- getEstimates, 3, 7, 8, 10
- getEstimates, nplr-method (getEstimates), 3
- getEstimates-methods (getEstimates), 3
- getFitValues (nplrAccessors), 8
- getFitValues, nplr-method (nplrAccessors), 8
- getFitValues-methods (nplrAccessors), 8
- getGoodness (nplrAccessors), 8
- getGoodness, nplr-method (nplrAccessors), 8
- getGoodness-methods (nplrAccessors), 8
- getInflexion (nplrAccessors), 8
- getInflexion, nplr-method (nplrAccessors), 8
- getInflexion-methods (nplrAccessors), 8
- getPar (nplrAccessors), 8
- getPar, nplr-method (nplrAccessors), 8
- getPar-methods (nplrAccessors), 8
- getStdErr (nplrAccessors), 8
- getStdErr, nplr-method (nplrAccessors), 8
- getStdErr-methods (nplrAccessors), 8
- getWeights (nplrAccessors), 8
- getWeights, nplr-method (nplrAccessors), 8
- getWeights-methods (nplrAccessors), 8
- getX (nplrAccessors), 8
- getX, nplr-method (nplrAccessors), 8
- getX-methods (nplrAccessors), 8
- getXcurve (nplrAccessors), 8
- getXcurve, nplr-method (nplrAccessors), 8
- getXcurve-methods (nplrAccessors), 8
- getY (nplrAccessors), 8
- getY, nplr-method (nplrAccessors), 8
- getY-methods (nplrAccessors), 8
- getYcurve (nplrAccessors), 8
- getYcurve, nplr-method (nplrAccessors), 8
- getYcurve-methods (nplrAccessors), 8
- nplr, 3, 4, 5, 8–11
- nplr-class (nplr), 5
- nplrAccessors, 4, 7, 8
- nplrAccessors, nplr-method (nplrAccessors), 8
- nplrAccessors-methods (nplrAccessors), 8
- overlay, 8, 10
- par, 8, 10
- plot.nplr, 4, 7, 9, 9, 11
- summary.nplr, 11